

---

Aluminium Tri-formate

<b>Aspect</b>	: White to cream coloured powder
<b>Basis</b>	: Aluminium Tri Formate
<b>Solid content</b>	: 95±1.0%
<b>Mineral Content</b>	: Al <sub>2</sub> O <sub>3</sub> 1 21-22%
<b>pH</b>	: In 10% aqueous solution, 3.5 – 4.5
<b>Solubility</b>	: Readily soluble with slight sediments
<b>Light Fastness</b>	: Good

**PROPERTIES :**

- It can be used for fixing water repellent and water proofing fat liquors.
- It gives good fixation to anionic dyes and increasing the dyeing brilliancy.
- Is suitable for white leather because it gives good whiteness to the leather.
- Improves buffing property and gives short nap for nubuck and suede leather.
- It has good tanning property so can be use along with chrome & other wet white tanning agents.

**APPLICATIONS :**

- |                      |   |
|----------------------|---|
| 1. Wet white tanning | :3 – 6% SWAEKASYN ALF, based on pelt weight           |
| 2. Chrome Tanning    | :1 – 3%SWAEKASYN ALF before Chrome, Based on pelt wt. |
| 3. Other Retanning   | :2 – 4% SWAEKASYN ALF, based on shaved weight         |
| 4. Fixing WaterProof | :2 – 3% SWAEKASYN ALF based on shaved weight          |